

APD 1000 C

Cummins
Akso
D+ &



ISO8528	GC,) &
SZUTEST	GC - \$\$\$
CE

2000/14/EC

&\$\$\$#(#

z) \$ z'z' D:

	"	"	"	"	Amp
400/230	1000,00	800,00	920,00	736,00	1327,00

Standard Specifications

...

...

ALTERNATOR

...

TRANSFER SWITCH

...

APD 1000 C

Cummins
Aksa
D+' &'



Manufacturer		Cummins											
Model		KTA 38-G2A											
		<table border="1"> <tr> <td>%\$\$</td> <td>"#</td> <td>"</td> </tr> <tr> <td>, -)</td> <td>"</td> <td></td> </tr> <tr> <td>0&\$\$<</td> <td>DQ</td> <td></td> </tr> </table>			%\$\$	"#	"	, -)	"		0&\$\$<	DQ	
%\$\$	"#	"											
, -)	"												
0&\$\$<	DQ												
	L	38,00											
	"	159 X 159											
		14,5:1											
	fl # ı	"# "	1500										
	fl ı	L	114,00										
		L	280,00										
AbsorbedAirDischargeReSourceKey.Text	' # "	67,00											
	' # "	1500											
	' # "	193,00											
	° C	536											
		24 V d.c.											
	Load	%\$\$ı	'+)ı)\$ı									
	# "	192,00	153,00	106,00									

		Aksa		
		AK7740		
	Hz	50		
	"	925		
7cg'		0,80		
		3		
	fl ı	400/230		
	A	1335		

		fl ı		fl ı	
	"	"	"	"	L
APD 1000 C	7950	4400	2060	2400	900
		fl ı		fl ı	
	"	"	"	"	L
AK 96	11500	7500	2300	2500	1500

